

THE MOTOROLA WAREHOUSING MOBILE COMPUTING PORTFOLIO



THE MOTOROLA SOLUTIONS MOBILE WAREHOUSE PORTFOLIO

When you choose Motorola, you get the peace of mind that comes with choosing an industry leader with well-tested and well-proven solutions as your technology partner. Every day, Motorola's Mobile Warehouse Solutions help organizations of every size proactively respond to customer demand, increase supply chain efficiency and successfully compete in today's fast-paced environment.

A RUGGED DESIGN AND INDUSTRY LEADING ERGONOMICS

While our devices are built to handle the demands of your toughest warehouse environments, they are also built for user comfort. You get reliable operation, even if the devices are dropped on concrete or used in driving rain, snow, summer heat, extreme winter cold, an industrial freezer or dusty warehouse.

INDUSTRY-LEADING ERGONOMICS FROM OUR AWARD-WINNING INDUSTRIAL DESIGN TEAM

Our rugged devices never compromise on comfort. Every one of our devices is built with the user in mind, with features that make it easy for your workers to hold and use our devices, all day long — our devices are well balanced, easy to securely hold without fatiguing, with keys that are sized and placed for easy one-handed operation and the intelligence to automatically adjust display lighting and sound to match environmental conditions.*

ANYWHERE, ANYTIME CAPTURE OF VIRTUALLY ANY TYPE OF DATA

With the ability to capture 1D and 2D bar codes (including GS1), direct part marks (DPM), photos, videos, signatures, documents, even RFID, Motorola mobile computers can capture whatever type of data is in use in your environment today — and tomorrow.

MOTOROLA'S UNRIVALED BAR CODE SCANNING TECHNOLOGY

The warehouse can be a tough place for bar codes; they get dirty, scuffed and hard to read. As the inventor of the entire bar code industry, we offer high performance 'scan and go' simplicity, able to capture even damaged and poorly printed bar codes without aligning bar code and scanner window.

EASY CENTRALIZED REMOTE MANAGEMENT OF YOUR MOTOROLA AND NON-MOTOROLA MOBILE DEVICES AND THEIR PERIPHERALS

Get your devices up and running, update applications, monitor the health of all devices and troubleshoot and resolve device issues — all without ever touching your mobile devices.

* Available ergonomic features vary by device and device type.

INDUSTRY LEADING SERVICE PLANS THAT COVER EVERYTHING — PERIOD.

With our optional Service from the Start with Comprehensive Coverage support plan, you get a unique all-inclusive program that sets the standard for post-deployment support. Not only does it cover normal wear and tear, it also covers internal and external components damaged through accidental breakage, as well as accessories that are included in the box. The result? No more unforeseen repair expenses to unexpectedly hit your budget — or increase the total cost of ownership (TCO).

SECURITY YOU CAN COUNT ON

Our Mobile Security Suite allows you to add the same security features that protect your wired and wireless network to your mobile devices — from a firewall to intrusion prevention, enforced authentication, data encryption, mobile VPNs for government grade security and more.

EXTRAORDINARY CONTROL OVER THE MOBILE DEVICE FEATURE SET

With Motorola Solutions' AppCenter, you choose which device features your workers can access, preventing personal use of devices — and protecting worker productivity.

EASY AND COST-EFFECTIVE APPLICATION DEVELOPMENT AND DEPLOYMENT

Our vast partner ecosystem offers ready-to-go and custom best-in-class applications to streamline virtually any business process in your warehouse operations. In addition, with Motorola Solutions' RhoMobile Suite, you can create one version of an application that can run on any device in your warehouse — regardless of operating system or screen size. Applications look, feel and act the same on all devices and can take advantage of whatever feature set is on each device. The result is a pure application simplicity that dramatically reduces application development and management time and cost. And with our Terminal Emulation application, your users can access your mainframe applications right out of the box.

HANDHELD MOBILE COMPUTERS

			HANDHELD MO	BILE COMPUTERS	
		TC70	OMNII XT15	MC9500-K	WORKABOUT PRO 4
		motorolasolutions com/TC70	motorolasolutions com/OmniiXT15	motorolasolutions.com/MC9500	motorolas olutions com/workshoutere/A
Deal mode, large 4 in leasthy and exceptions and exception promised large presentation of the book supports of PT out of the book visible distribution of the book visible distribution of visible distribution of the book visible distribution of visible visible distribution of visible visible distribution of visible	GENERAL DESCRIPTION	motorolasolations.com/ 1070	motorolasolutions.com/ ominiA 113	motorolasolutions.com/wo3300	motororasorutions.com/ workaboutpro4
Picking •<	Device Highlights	 Dual-mode, large 4.7 in touch panel Comprehensive 1D/2D data capture Supports PTT out of the box VolP client ready for PBX functionality (North America) Robust accessory family 	 Standard, freezer and non-incendiary models Supports voice and data Most demanding applications Cellular, Wi-Fi and Narrowband Modular design, field 	Demanding applicationsSupports voice and data	 Modular for superior ROI — add virtually any feature on site (no need for depot return) 8 MP Camera Long range scanning option Demanding environments
Recolving and put-away •	APPLICATIONS				
Circios-docking •	Picking	•	•	•	•
Shipping •	Receiving and put-away	•	•	•	•
Pekking •<	Cross-docking	•	•	•	•
Returns •<	Shipping	•	•	•	•
Manager dashboart •	Packing	•	•	•	•
USER AND APPLICATION CONSIDERATIONS Weight 13.3 oz/376 g XT15: 21.44 oz/610 g 22 oz/623 g Short: 16.2 oz/461 g cong: 18.6 oz/526 g Display 47 in. color HD touchscreen 3.7 in. VGA color touchscreen 4.7 in. VGA Burn Donnact S.8 de ya alpha; 55-key alpha; 55-key alpha; 55-key alpha; 68-key numeric 3.8 in. Alpha primary; numeric telephony, numeric telephony, numeric telephony, numeric alculator, alphanumeric 4.0 plan untertic touchscreen 10, 20, 10 model? 4.0 plan untertic touchscreen 10, 20, 3 m Pcolor camera 10, 20, 3 m Pcolor camera 10, 20, 3 m Pcolor camera <t< td=""><td>Returns</td><td>•</td><td>•</td><td>•</td><td>•</td></t<>	Returns	•	•	•	•
Weight 13.3 oz/376 g XT15:71.44 oz/610 g XT15 Freezer: 29.4 oz/834 g 22 oz/623 g Short: 16.2 oz./461 g Long: 18.6 oz/526 g Display 4.7 in. color HD touchscreen 3.7 in. VGA color touchscreen 3.7 in. VGA color touchscreen 3.7 in. VGA Processor 1.7 GHz 800 MHz 806 MHz 1 GHz Keypad Dn-screen (vitual keypad) 55-key alpha; 55-key alpha; 55-key alpha; 66-key QWERTY; 36-key numeric: 34-key numeric: 34-	Manager dashboard	•	•	•	•
Weight 13.3 oZ./37 og XT15 Freezer: 29.4 oz./834 g ZZ 0Z./623 g Long: 18.6 oz./526 g Display 4.7 in. color HD touchscreen 3.7 in. VGA color touchscreen 4.0 phap primary, numeric telephony, numeric calculator, alphanumeric Alphanumeric (long model); QWERTY or Numeric (short model) Bar code scanning and data capture 1D/2D, extended range; alberty of Numeric (short model) 4.0 phap primary, numeric calculator, alphanumeric alphanumeric Alphanumeric (long model); QWERTY or Numeric (short model) Cellular connectivity No Optional 1D, 2D, 3 MP color camera DtD, Jay MP color camera DtD, Jay Jay MP color camera DtD, Jay	USER AND APPLICATION C	ONSIDERATIONS			
Processor	Weight	13.3 oz./376 g		22 oz./623 g	
Keypad On-screen (virtual keypad) 69-key alpha; 66-key olwEnTY; 36-key numeric; 34-key numeric; 34-ke	Display	4.7 in. color HD touchscreen	3.7 in. VGA color touchscreen	3.7 in. VGA color touchscreen	3.7 in. VGA
Keypad Unseren (virtual keypad) 66-key QWERTY; 36-key numeric: 34-key numeric: 34-key numeric calculator, alphanumeric (long modell)? QWERTY or Numeric (short modell) Alphanumeric telephony, numeric calculator, alphanumeric (long modell)? QWERTY or Numeric (short modell) Bar code scanning and data capture 1D/2D, extended range; 8 MP color camera; NFC Optional 1D, 2D, 3 MP color camera 1D, 2D, 3 MP color camera 1D, 2D, long range scanning Cellular connectivity No Optional: 2.5G GSM/GPRS/EDGE; 3 MC Jay/b/g/n Modular 3.5G Dual-WAN (GSM HSDPA and CDMA EVDO Rev A) Optional UMTS/HSPA+ WAN radio ² with GPS receiver Wi-Fi 802.11a/b/g/n/d/h/hi IEEE 802.11a/b/g/n 802.11a/b/g 802.11a/b/g/n	Processor	1.7 GHz	800 MHz	806 MHz	1 GHz
and data capture 8 MP color camera; NFC 3 MP color camera 1U, 2U, 3 MP color camera 1U, 2U, 10ng range scanning Cellular connectivity No Optional: 2.5 G GSM/GPRS/EDGE; 3.86 HSPA+ Modular 3.5G Dual-WAN (GSM HSVPA+ WIN radio² with GPS receiver Optional UMTS/HSPA+ WAN radio² with GPS receiver Wi-Fi 802.11a/b/g/n/d/h/i IEEE 802.11a/b/g/n 802.11a/b/g 802.11a/b/g/n 802.11a/b/g Narrowband No No No No Bluetooth • • • • Voice support Workforce Connect PTT Express Workforce Connect Voice Client* Cellular and VoWLAN Cellular and VoWLAN Push-to-Talk – VolP over Wi-Fi² Extra security features User authentication and lockdown User authentication and lockdown FIPS 140-2 certification Modular LF/HF/UHF RFID Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; optional GPS	Keypad		66-key QWERTY; 36-key numeric;		
Vi-Fi 802.11a/b/g/n/d/h/i IEEE 802.11a/b/g/n 802.11a/b/g 802.11a/b/g 802.11a/b/g/n Narrowband No UHF bands: 403 - 470 MHz No No Bluetooth • • • • Voice support Workforce Connect PTT Express Workforce Connect Voice Client* Cellular and VoWLAN Cellular and VoWLAN Push-to-Talk – VolP over Wi-Fi² Extra security features User authentication and lockdown User authentication and lockdown FIPS 140-2 certification Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; optional HF RFID reader GPS; Integrated UHF tag for asset tracking Modular LF/HF/UHF RFID attachments RUGGED DESIGN B.5 ft/2 m 6 ft./1.8 m	•			1D, 2D, 3 MP color camera	1D, 2D, long range scanning
Narrowband No UHF bands: 403 - 470 MHz No No Bluetooth ● ● ● ● Voice support Workforce Connect PTT Express Workforce Connect Voice Client** Cellular and VoWLAN Cellular and VoWLAN Push-to-Talk – VoIP over Wi-Fi³ Extra security features User authentication and lockdown FIPS 140-2 certification Modular LF/HF/UHF RFID Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; optional HF RFID reader GPS; Integrated UHF tag for asset tracking Modular LF/HF/UHF RFID attachments RUGGED DESIGN FURTHER METERS (ADMINISTRATION of the MINISTRATION of the MINISTRA	Cellular connectivity	No	•	•	•
Bluetooth ● ● ● ● ● Voice support Workforce Connect PTT Express Workforce Connect Voice Client* Cellular and VoWLAN Cellular and VoWLAN Push-to-Talk – VoIP over Wi-Fi³ Extra security features User authentication and lockdown User authentication and lockdown FIPS 140-2 certification Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; optional GPS; optional FRFID reader GPS; Integrated UHF tag for asset tracking Modular LF/HF/UHF RFID attachments RUGGED DESIGN Torp Tested 6 ft./1.8 m 9 ft./1 m tumbles 9 ft./20° to 50° C 1 ft./2 m ft./20° ft./20° to 50° C 4° to 122° F/-20° to 50° C 4° to 122° F/-20° to 50° C 4° to 122° F/-20° to 50° C 1 ft./1 m tumbles 9 ft./20° to 50° C 1 ft./20° ft./20° to 50° C 1 ft./20° ft./20° to 50° C 1 ft./20° ft./20° to 50	Wi-Fi	802.11a/b/g/n/d/h/i	IEEE 802.11a/b/g/n	802.11a/b/g	802.11a/b/g/n
Voice support Workforce Connect PTT Express Workforce Connect Voice Client* Cellular and VoWLAN Cellular and VoWLAN Push-to-Talk – VolP over Wi-Fi³ Extra security features User authentication and lockdown User authentication and lockdown FIPS 140-2 certification Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; optional HF RFID reader GPS; Integrated UHF tag for asset tracking Modular LF/HF/UHF RFID attachments Prop Tested 6 ft./1.8 m 6.5 ft./2 m 6 ft./1.8 m 6 ft./1.8 m Tumble Tested 2,000 3.28 ft./1.0 m tumbles 4000 3.28 ft./1 m tumbles Sealing IP67 IP65/IEC 60529 IP67 IP65 Operating Temperature -4° to 122° F/-20° to 50° C XT15F, XT15ni and XT15F Chiller: -4° to 122° F/-20° to 50° C XT15F Artic: -22° to 122° F/-30° to 50° C -4° to 122° F/-20° to 50° C XT15F Artic: -22° to 122° F/-30° to 50° C -4° to 122° F/-20° to 50° C -4° to 122° F/-20° to 50° C	Narrowband	No	UHF bands: 403 - 470 MHz	No	No
Workforce Connect Voice Client* Extra security features User authentication and lockdown User authentication and lockdown Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; O	Bluetooth	•	•	•	•
Other features ShareCradle, trigger handle, MSR reader and DEX cable Optional GPS; optional HF RFID reader GPS; Integrated UHF tag for asset tracking Modular LF/HF/UHF RFID attacking RUGGED DESIGN Drop Tested 6 ft./1.8 m 6.5 ft./2 m 6 ft./1.8 m 6 ft./1.8 m Tumble Tested 2,000 3.28 ft./1.0 m tumbles 4000 3.28 ft./1 m tumbles Sealing IP67 IP67/IP65/IEC 60529 IP67 IP65 Operating Temperature A° to 122° F/-20° to 50° C XT15F, XT15ni and XT15F Chiller: -4° to 122° F/-20° to 50° C XT15F Artic: -22° to 122° F/-30° to 50° C -4° to 122° F/-20° to 50° C -4° to 122° F/-20° to 50° C	Voice support	•	Cellular and VoWLAN	Cellular and VoWLAN	Push-to-Talk — VoIP over Wi-Fi ³
RUGGED DESIGN From asset tracking attackments Drop Tested 6 ft./1.8 m 6.5 ft./2 m 6 ft./1.8 m 6 ft./1.8 m Tumble Tested 2,000 3.28 ft./1.0 m tumbles 4000 3.28 ft./1 m tumbles Sealing IP67 IP67/IP65/IEC 60529 IP67 IP65 Operating Temperature 4° to 122° F/-20° to 50° C XT15, XT15ni and XT15F Chiller: -4° to 122° F/-20° to 50° C 4° to 122° F/-20° to 50° C -4° to 122° F/-20° to 50° C	Extra security features	User authentication and lockdown	User authentication and lockdown	FIPS 140-2 certification	
Drop Tested 6 ft./1.8 m 6.5 ft./2 m 6 ft./1.8 m 6 ft./1.8 m Tumble Tested 2,000 3.28 ft./1.0 m tumbles 4000 3.28 ft./1 m tumbles Sealing IP67 IP67/IP65/IEC 60529 IP67 IP65 Operating Temperature 4° to 122° F/-20° to 50° C XT15, XT15ni and XT15F Chiller:	Other features	. 66			
Tumble Tested 2,000 3.28 ft./1.0 m tumbles 4000 3.28 ft./1 m tumbles Sealing IP67 IP67/IP65/IEC 60529 IP67 IP65 Operating Temperature -4° to 122° F/-20° to 50° C XT15, XT15ni and XT15F Chiller:	RUGGED DESIGN				
Sealing IP67 IP67/IP65/IEC 60529 IP67 IP67 IP65 Operating Temperature -4° to 122° F/-20° to 50° C XT15, XT15ni and XT15F Chiller:	Drop Tested	6 ft./1.8 m	6.5 ft./2 m	6 ft./1.8 m	6 ft./1.8 m
Operating Temperature -4° to 122° F/-20° to 50° C XT15, XT15ni and XT15F Chiller: -4° to 122° F/-20° to 50° C XT15F Artic: -4° to 122° F/-20° to 50° C XT15F Artic:	Tumble Tested	2,000 3.28 ft./1.0 m tumbles		4000 3.28 ft./1 m tumbles	
Operating Temperature -4° to 122° F/-20° to 50° C	Sealing	IP67	IP67/IP65/IEC 60529	IP67	IP65
Shock and Vibration Tested Yes Yes Yes Yes	Operating Temperature	-4° to 122° F/-20° to 50° C	-4° to 122° F/-20° to 50° C XT15F Artic:	-4° to 122° F/-20° to 50° C	-4° to 122° F/-20° to 50° C
	Shock and Vibration Tested	Yes	Yes	Yes	Yes

^{*} Supported in North America.

HANDHELD MOBILE COMPUTERS (CONT.) **GUN-STYLE HANDHELD MOBILE COMPUTERS** MC3200-R/S MC2100 **OMNII XT15** MC9200/MC9190-G













motorolasolutions.com/MC3200

motorolasolutions.com/MC2100

motorolasolutions.com/Omnii XT15

motorolasolutions.com/MC9200 motorolasolutions.com/MC9190

GENERAL DESCRIPTION

Device Highlights

- Rugged handheld
- Supports voice and data
- Two models: small and light straight shooter (S) or adjustable rotating scanning head (R)
- Choice of operating systems: Windows Embedded Compact

Yes

- Rugged handheld
- Supports voice and data
- Lightweight and optimized for one-hand use
- Value-priced
- Extreme industrial rugged design
- Gun-style ergonomics for scanning-intensive apps
- Standard, freezer and non-incendiary models
- Supports voice and data
- Long range scanning options
- Three scan engine options and
- Very rugged handheld
- Gun-style ergonomics for scanning-intensive apps
- Supports voice and data
- Long range scanning options
- Superior customization: six scan engine options and six interchangeable keypads

Yes

	Windows Embedded Compact 7.0 (Standard or Premium¹) or		 Three scan engine options and nine keyboard options — 	six interchangeable keypadsPower to support next
	Android 4.1 (Premium)		all field upgradeable	generation mobile applications
APPLICATIONS			`	
Picking	•	•	•	•
Receiving and put-away	•	•	•	•
Cross-docking	•	•	•	•
Shipping	•	•	•	•
Packing	•	•	•	•
Returns	•	•	•	•
Manager dashboard	•		•	•
USER AND APPLICATION	CONSIDERATIONS			
Weight	R: 13.13 oz./372 g; S: 12.88 oz./365 g	8.32 oz./236 g	29.42 oz./834 g	27 oz./765 g
Display	3 in. color TFT touchscreen	2.8 in. QVGA, touchscreen option	3.7 in. VGA color touchscreen	3.7 in. VGA color touchscreen
Processor	Standard: 800 MHz dual core Premium: 1 GHz dual core	624 MHz	800 MHz	MC9200: Dual core 1GHz MC9190-G: 806 MHz
Keypad	28-key numeric; 38-key shifted alpha, 48-key alphanumeric	27-key numeric	59-key alpha; 55-key alpha; 66-key QWERTY; 36-key numeric; 34-key numeric	Six interchangeable keypads: 28-, 43- and 53-key; Terminal Emulation (5250, 3270, VT)
Bar code scanning and data capture	1D, 2D, HD (high density)	1D, 2D	Optional 1D, 2D, long range scanning/ imaging plus 3 MP color camera	1D, 2D, DPM, long range scanning/imaging
Cellular connectivity	No	No	Optional: 2.5G GSM/GPRS/EDGE; 3.8G HSPA+	No
Wi-Fi	802.11a/b/g/n	802.11b/g/n	802.11a/b/g/n	MC9200: 802.11a/b/g/n MC9190-G: 802.11a/b/g
Narrowband	No	No	UHF bands: 403 - 470 MHz	No
Bluetooth	•	•	•	•
Voice support	VoWLAN	VoWLAN	Push-to-talk and VoWLAN	VoWLAN
Extra security features	FIPS 140-2 certification⁴		User authentication and lockdown	FIPS 140-2 certification
Other features			Optional GPS; optional HF RFID reader	Integrated UHF RFID tag for asset tracking
RUGGED DESIGN				
Drop Tested	5 ft./1.5 m	4 ft./1.2 m	6.5 ft./2 m	6 ft./1.8 m
Tumble Tested	1,000 1.64 ft./0.5 m tumbles	1,000 1.64 ft./0.5 m tumbles		4,000 3.28 ft./1 m tumbles
Sealing	IP54	IP54	IP67/IP65/IEC 60529	IP64
Operating Temperature	-4° to 122° F/-20° to 50° C	14° F to 122° F/-10° to 50° C	XT15, XT15ni and XT15F Chiller: -4° to 122° F/-20° to 50° C XT15F Artic: -22° to 122° F/-30° to 50° C	-4° to 122° F/-20° to 50° C

Yes

Shock and Vibration

GUN-STYLE HANDHELD MOBILE COMPUTERS (CONT.)

RFID GUN-STYLE HANDHELD MOBILE COMPUTERS

ENTERPRISE TABLET

MC3200-G

MC9190-Z RFID

ET1









motorolasolutions.com/MC3200

motorolasolutions.com/mc9190z

motorolasolutions.com/ET1

GENERAL DESCRIPTION

Device Highlights

- Rugged handheld
- Gun-style ergonomics for scanningintensive apps
- Supports voice and data
- Choice of Windows Embedded Compact 7.0 (Standard or Premium) or Android 4.1 (Premium)
- Very rugged handheld
- Gun-style ergonomics for scanningintensive apps
- Robust RFID locationing technology — unique combination of audible and visual cues enable easy pin-point location instead of general proximity
- Truly enterprise-ready
- Android tablet
- As sleek and easy to use as popular consumer tablets, yet loaded with enterprise features that deliver durability, security, manageability, flexibility and more
- Wi-Fi for anywhere

		Long range scanning options	on-premise connectivity
APPLICATIONS			
Picking	•	•	
Receiving and put-away	•	•	•
Cross-docking	•	•	
Shipping	•	•	
Packing	•	•	
Returns	•	•	•
Manager dashboard			•
USER AND APPLICATION (CONSIDERATIONS		
Weight	18 oz./509 g	35.4 oz./1 kg	1.4 lbs/.63 kg
Display	3 in. color TFT touchscreen	Touchscreen 3.7 in VGA color	Capacitive multi-touch 7 in. with Corning® Gorilla® Glass
Processor	Standard: 800 MHz dual core Premium: 1 GHz dual core	806 MHz	Dual core 1 GHz each plus graphics accelerator
Keypad	28-key numeric; 38-key shifted alpha, 48-key alphanumeric	28, 43 and 53-key options	Virtual; Bluetooth
Bar code scanning and data capture	1D, 2D, HD (high density)	1D extended range 1D, 2D, RFID, imaging	1D, 2D, photos, video, signatures, documents
Cellular connectivity	No	No	Yes
Wi-Fi	802.11a/b/g/n	802.11a/b/g	802.11a/b/g/n
Narrowband	No	No	No
Bluetooth	•	•	•
Voice support	VoWLAN	N/A	VoWLAN
Extra security features	FIPS 140-2 certification ⁴	FIPS 140-2 certification	
Other features		Robust pin-point item locationing technology	Swivel handstrap rotates 360° for easy portrait to landscape rotation
RUGGED DESIGN			
Drop Tested	5 ft./1.5 m	6 ft./1.8 m	4 ft./1.2 m
Tumble Tested	1,000 1.64 ft./0.5 m tumbles	4,000 1.64 ft./0.5 m tumbles	N/A
Sealing	IP54	IP64	IP54
Operating Temperature	-4° to 122° F/-20° to 50° C	-4° to 122° F /-20° to 50° C	32° to 122° F /0° to 50° C
Shock and Vibration	Yes		Yes

VEHICLE MOUNT MOBILE COMPUTERS VC5090 VC6090 **VH10** VC70N0 motorolasolutions.com/VC5090 motorolasolutions.com/VC6090 motorolasolutions.com/VH10 motorolasolutions.com/VC70N0 **GENERAL DESCRIPTION Device Highlights** · Rugged fixed mount mobile · Rugged fixed mount · Ultra-rugged fixed mount · Ultra-rugged fixed mount mobile computer for material mobile computer for material computer for materials mobile computer handling vehicles · Small form factor for tighthandling vehicles handling vehicles spaced lift trucks and carts • Freezer-ready Freezer ready Freezer-ready • Large 12.1 in. screen for · Supports voice, data and bar • 8 in. half screen with integrated • Powerful processor to handle easy viewing of data-heavy code scanning via Motorola's full alphanumeric keyboard; graphics-rich applications applications corded or cordless scanner 12 direct Function keys for superior • Large 10 in. screen for easy viewing of information-rich applications · Supports voice picking process automation • Supports bar code scanning via · Supports voice, data and bar code · Supports voice, data and bar code Motorola Solutions corded or scanning via Motorola Solutions scanning via Motorola Solutions cordless scanners corded or cordless scanner corded or cordless scanner **APPLICATIONS Picking** • • • Receiving and put-away **Cross-docking** • • **Shipping** • • • **Packing** • Returns • Manager dashboard **USER AND APPLICATION CONSIDERATIONS** Weight 14.5 lbs./6.85kg 4.85 lbs/2.2 kg 8.1 lbs./3.66 kg 9.4 lbs/4.3 kg 8 in. color; 800 x 480 touchscreen; 10.4 in. color XGA backlit Display 12.1 in. SVGA 6.5 in color VGA touchscreen superbright 640 NITs touchscreen; 600 NITs 800 MHz Dual Core 1GHz **Processor** 624 MHz 624 MHz Three optional keyboards: Full 67 key QWERTY Full heated and sealed 65-key Full 65-key QWERTY or AZERTY; Keypad QWERTY 65-key **QWERTY or AZERTY** or AZERTY 21-key side-mounted Numeric Bar code scanning via Motorola's Bar code scanning cordless or corded scanners and data capture cordless or corded scanners cordless or corded scanners cordless or corded scanners **Cellular connectivity** Νn Νn Nο Nο Wi-Fi 802.11a/b/g 802.11a/b/g 802.11a/b/g/n 802.11a/b/g/n Narrowband No No UHF bands: 403 - 470 MHz No Bluetooth • Voice support Voice picking, VoWLAN Voice picking, VoWLAN VoWLAN Voice picking, VoWLAN **Extra security features** Three heaters, temperature Temperature, motion Heated screen Other features sensors, motion sensor, and light sensors 30 programmable keys **RUGGED DESIGN** N/A (mounted) N/A (mounted) N/A (mounted) **Drop Tested** N/A (mounted) **Tumble Tested** N/A (mounted) N/A (mounted) N/A (mounted) N/A (mounted) IP66 Sealing IP64 IP66 IP66 -22° to 122° F/-30° to 50° C -4° to 140° F/-20° to 60° C -22° to 122° F/-30° to 50° C -22° to 122° F/-30° to 50° C **Operating Temperature Shock and Vibration** Yes Yes Yes Yes

	VEHICLE MOUNT MOBILE COMPUTERS		WEARABLE MOBILE COMPUTERS	
	8515	8585/8595	WT41N0	WT41N0 VOW
	motorolasolutions.com/8515	motorolasolutions.com/8585	motorolasolutions.com/WT41N0	motorolasolutions.com/WT41N0VOW
GENERAL DESCRIPTION				
Device Highlights	Rugged fixed mount mobile computer for material handling vehicles 6.4 in. screen with integrated full alphanumeric keyboard and 10 direct Function keys for superior process automation Supports voice and data Supports bar code scanning via Motorola Solutions corded or cordless scanner	Rugged fixed mount mobile computer for material handling vehicles Choice of Windows® XP or Windows® 7 operating system provides full PC functionality Freezer ready Supports voice and data Supports bar code scanning via Motorola Solutions corded or cordless scanner	Rugged wearable Hands-free design for maximum productivity in high-volume scanning environments Hands-free text and voice-directed tasks Compatible with corded and cordless wearable scanners	Rugged wearable Hands-free design for maximum productivity in high-volume scanning environments Simple, affordable tool for voice-directed tasks Compatible with corded and cordless wearable scanners
APPLICATIONS				
Picking	•	•	•	•
Receiving and put-away	•	•	•	•
Cross-docking	•	•	•	•
Shipping	•	•	•	•
Packing	•	•	•	•
Returns	•	•	•	•
Manager dashboard USER AND APPLICATION	CONCIDEDATIONS			
USER AND APPLICATION	CONSIDERATIONS	8585: 6.6 lb / 3 kg		
Weight	2.9 lbs./1.31 kg	8595: 7.7 lb / 3.5 kg	11.3 oz./320 g	12.2 oz./346 g
Display	6.4 in. color VGA	8585: 10.4 in. color SVGA 8595: 12.1 XGA	Touchscreen 2.8 in. QVGA color	N/A
Processor	312 MHz	Choice of single core 1.1 GHz or dual core 1.0 GHz	Dual core 1 GHz	Dual core 1 GHz
Keypad	58-key alphanumeric	72- and 82-key options	23-key alphanumeric	N/A
Bar code scanning and data capture	Bar code scanning via Motorola's cordless or corded scanners	Bar code scanning via Motorola's cordless or corded scanners	Bar code scanning via Motorola's wearable cordless or corded scanners	Bar code scanning via Motorola's wearable cordless or corded scanners
Cellular connectivity	No	No	No	No
Wi-Fi	802.11b/g	802.11a/b/g/n	802.11a/b/g/n	802.11a/b/g/n
Narrowband	No	No	No	No
Bluetooth	•		•	•
Voice support	Voice picking, VoWLAN	Voice picking, VoWLAN	VoWLAN, voice picking via cordless or corded headset	VoWLAN, voice picking via corded or cordless headset
Extra security features				
Other features			Comfortable hip or wrist mounting	Comfortable hip or wrist mounting
RUGGED DESIGN				
Drop Tested	N/A (mounted)	N/A (mounted)	4 ft./1.2 m	4 ft./1.2 m
Tumble Tested	N/A (mounted)	N/A (mounted)	1,000 1.64 ft./0.5 m tumbles	1,000 1.64 ft./0.5 m tumbles
Sealing	IP65	IP66; IP67	IP54	IP54
Operating Temperature	-4° to 122° F /-20° to 50° C	-22° to 122° F /-30° to 50° C	-4° to 122° F /-20° to 50° C; -22° to 122° F /-30° to 50° C* (* with optional freezer pouch)	-4° to 122° F /-20° to 50° C; -22° to 122° F /-30° to 50° C* (* with optional freezer pouch)

ACCESSORIES: WEARABLE SCANNERS AND HEADSET

RS419 RCH51 RS507







motorolasolutions.com/RS419

motorolasolutions.com/RS507

motorolasolutions.com/RCH51

GENERAL DESCRIPTION

Device Highlights

- Tiny hands-free corded ring imager for 1D and 2D bar codes
- Worn on the finger (with or without gloves)
- Tiny hands-free Bluetooth wireless ring-style imager for 1D and 2D bar codes
- · Best-in-class scanning performance
- Most rugged ring-style scanner
- Two-finger design (can be
- Rugged cabled headset for handsfree voice-directed applications
- · Lightweight and comfortable
- Compatible with WT4XXX, WTXXX VOW, MC9500-K, MC3100 and other Motorola mobile computers

	worn with or without gloves)			
USER AND APPLICATION C	ONSIDERATIONS			
Weight	2.0 oz./56.7 g	4.3 oz./121.4 g	3.9 oz./111 g	
Bar code scanning and data capture	1D	1D, 2D	N/A	
Corded or Cordless	Corded	Bluetooth cordless, Corded	Corded	
Other features	Multiple field replaceable components	Multiple field replaceable components	Adjustable one-size-fits-all headband	
RUGGED DESIGN				
Drop Tested	4 ft./1.2 m	6 ft./1.8 m	6 ft./1.8 m	
Tumble Tested	None	None	1,000 1.64 ft./0.5 m tumbles	
Sealing	IP54	IP54	IP67	
Operating Temperature	-4° to 122° F/-20° to 50° C	-4° to 131° F/-20° to 55° C	-22° to 122° F/-30° to 50° C	



TAILOR YOUR WEARABLE SOLUTION WITH A TINY AND LIGHTWEIGHT RING-STYLE SCANNER AND A RUGGED HEADSET FOR VOICE PICKING.

- 1. MC3200 Premium models offer increased memory, faster processor and integrated sensor technology.
- 2. Data only in the Americas.
 3. In the Americas the Workabout Pro 4 is not approved to be used with any VoIP application using Wide Area Network (WAN) or Wireless Local Area Network (WLAN).
- 4. FIPS 140-2 certified for Android. Embedded Compact 7 will be certified in Q4 2014.

Part number: BRO-WAREHS-PORT. Printed in USA 09/14. MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2014 Motorola Solutions, Inc. All rights reserved.

