Panasonic



ARBITRATOR 360° HD

- Full HD 1080p High-quality Video Evidence Capture
- Unparalleled 360° Recording and Viewing
- Low-light Technology for Viewing in Darkness
- Industry-leading 65° Wide-angle Lens and up to 360x Zoom for Maximum Field of View
- SafeServ[™] Software Is Compatible with Previous Arbitrator Models and the Panasonic Wearable Camera
- Supports up to Two 512GB Solid State Drives
- Wireless Microphone System Can Transmit Quality Audio up to 1 Mile from the Receiver
- Provides the Capability to Manage Non-Arbitrator Files

INTRODUCING THE REVOLUTIONARY ARBITRATOR 360° HD—THE CLEAR CHOICE FOR MOBILE EVIDENCE CAPTURE.

The Arbitrator 360°[™] HD rugged in-car digital video recording system leads the industry in image quality for unmatched critical mobile video evidence capture. Its Full HD 1080p front camera delivers amazing clarity and ultra-accurate color representation, capturing a 65° field of view with enhanced low-light zooming. Up to four additional cameras covering the sides and rear record in 720p HD with 150° horizontal and 93° vertical fields of view to maximize situational awareness. Built on the foundation of Panasonic's industry-leading i-PRO surveillance cameras, the Arbitrator 360° HD delivers the trusted mobile digital video evidence that first responders need for confidence in the courtroom, improved officer safety and trusted community relationships.

The Arbitrator 360° HD system is engineered to work with Panasonic's SafeServ[™] Evidence Management Software Suite, which provides a comprehensive, secure and easily customized digital evidence management system. With the ability to manage digital evidence, including still images, IP surveillance video footage and video from Panasonic's WV-TW310 wearable camera systems, SafeServ also protects your investment by ensuring compatibility with previous Arbitrator models.



Panasonic

ARBITRATOR 360° HD

MIL-STD-810G compliant

offering an unparalleled 360° view

Rugged mount designed to withstand extreme heat and vibration

Front camera provides H.264 Full HD video (1080p) high-quality image resolution
 Interoperable with a Toughbook® PC or other vehicle-mounted PC
 Wide-angle lens provides an exceptional field of view

Up to 5 cameras can be recorded and viewed simultaneously using split screen.

Panasonic

VIDEO PROCESSING UNIT (WJ-VR30)

	GENERAL	
	 Operating Temperature 	-10°C to 50°C
	 Storage Temperature 	-20°C to 60°C
	 Operating Humidity 	10% to 80% (no condensation)
	Power Source	12V DC
		(Guaranteed operating voltage: 10V
		to 14V)
	Power Consumption	56.4W (with 5 cameras) 12V / 4.7A (max)
ted	 Voltage/Current Dimensions 	7"(W) x 3.44"(H) x 6.1"(D)
	 Weight 	4 0 lbs
idence manage-	- Weight	4.0 lbs.
	RECORDING	
	Recording Media	SSD
	 Capacity 	Supports up to (2) 512GB
	 SSD Slot 	With electromagnetic lock
	INTERFACE	
	 5-10/100Mbps Ethernet Ports 	
/ 320 x 80, 30fps	for up to five cameras	
	 2-1Gbps Ethernet Ports for PC/Upload 	
	 Optional Wireless LAN 1 (for Upload) 	802.11n 2 x 2 (2.4GHz, 5GHz)
n [High])	 Serial Port (for Radar Gun) 	RS-232C
n [High])	GPI0	16 Inputs, 4 Outputs
	GPS	Built-in
	 Power Connector (12V DC) 	(+)/(-)/(ACC)/(N.C.)
	 Analog Audio Input 1 (for In-Car Mic) 	–50 dBV, 3k Ω Unbalanced
	 Analog Audio Input 2 (for W-Mic) 	–10 dBV, 25k Ω Unbalanced
	FRONT PANEL	
	Buttons	REC, STOP
	 Indicator 	REC, READY, BUSY, UPLOAD,
	marcator	SSD1, SSD2, LAN, PC, WIRELESS1,
onditions		WIRELESS2, PoE, LINK/ACT
	WIRFI FSS MICROPHONE	

WIRELESS MICROPHONE

FEATURES Frequency Bandwidth

- Frequency Bandwidth
 Communication Range
- Talk Time

WIRELESS TRANSMITTER

- ButtonsIndicators (Battery Power Level)
- Indicators (Tx Status)
- Sampling Frequency
- WIRELESS RECEIVER
- Charging Status IndicatorAuxiliary Control of In-vehicle Devices
- Real time Status Updates with VPU

SOFTWARE SUITE

- SafeServ[™] APPLICATION
- Administrator-controlled System Configuration
- Flexible Storage OptionsFlexible Operating Environment
- Single Platform Evidence Management

CommandR[™] APPLICATION

- Provides Full System Control
 Runs on Windows® OS
- Allows Documentation and Classification of Event



Front Camera

Video Processing Unit Rear Seat Camera



902MHz-928MHz ISM Band

Out of Range, Sync, Mute, Recording

5000 ft. (in Open Field)

REC, MUTE, AUX

Green (50%-100%) Amber (15%-49%)

Red (Under 15%)

12 Hours

16KHz



Up to 3 channels of audio can be recorded simultaneously Low-light technology allows for viewing in near complete darkness Wireless microphone transmits high-quality audio up to 1 mile from the receiver Recorded files can be archived on a local/external hard drive or DVD-R and transmi via Wi-Fi or other high-speed wireless networks Provides an easy-to-use graphical interface to maximize officer safety and flexible ement in the vehicle

FRONT CAMERA (WV-VC30)

DURABILITY

KEY FEATURES

FEATURES	COMPONENT	SPECIFICATION
	Resolution	Imaging mode: 16:9
		H.264 1920 x 1080 / 1280 x 720 / 640 x 360 / 320 x 80, 30fps
	Zoom Range	30x Optical; 12x Digital
	Image Sensor	1/3 MOS
	Low-light Capability	Color: 0.5 lx (F1.6, Shutter: 1/30s, AGC: On [High])
		B/W: 0.02 lx (F.1.6, Shutter: 1/30s, AGC: On [High])
	Angular Field of View	Horizontal: 2.3-65.1°
		Vertical: 1.3-38.4°
	 Auto Adjustments 	Focus, White Balance
	 Day/Night 	Off/Auto
	AGC	On (Low) / On (Mid) / On (High) / Off
	 Weight 	1.35 lbs.
	Dimensions	3.58"(W) x 2.95"(H) x 4.84"(D)
		(excluding mount and projecting parts)
CONTROLS	 Manual Zoom 	Mode Button to Optimize for Lighting Conditions
	 Auto Zoom 	Home Button
	 Auto Focus 	Control Camera Button Backlight
	Record	Front and Rear Record Indication

REAR SEAT CAMERA (WV-VC31)

COMPONENT FEATURES SPECIFICATION Imaging mode: 16:9 H.264 1280 x 720 / 640 x 360 / 320 x 180, 30fps (max) Resolution Image Sensor 1/4 MOS Low-light Capability Color: 1.5 lx B/W: 0.0 lx (when the IR-LED is lit) Infrared Auto Angular Field of View Horizontal: 150° Vertical: 93° Auto Adjustments White Balance Day/Night Auto AGC Auto Wide Dynamic Range Auto Weight 0.79 lb Dimensions 3.94"(W) x 1.69"(H) x 1.85"(D) (excluding mount and projecting parts)

SIDE VIEW CAMERA (WV-VC32)

FEATURES

- COMPONENT Resolution
- Image Sensor
 Low-light Capability
- Angular Field of View
- Auto AdjustmentsDay/Night
- AGC
- Wide Dynamic RangeWeight
- Dimensions

SPECIFICATION

Inaging mode: 16:9 H.264 1280 x 720 / 640 x 360 / 320 x 180, 30fps (max) 1/4 MOS Color: 1.5 lx B/W: 1.0 lx Horizontal: 150° Vertical: 93° White Balance Auto Auto 0.62 lb. 3,94"(W) x 1.69"(H) x 1.85"(D) (excluding mount and projecting parts)

1.800.662.3537 us.panasonic.com/arbitrator360hd

Panasonic is constantly enhancing product specifications and accessories. Specifications subject to change without notice. Trademarks are property of their respective owners. ©2014 Panasonic Corporation of North America. All rights reserved. Arbitrator 360 HD Spec Sheet_08/14