

HD NVR4 Premium

Avigilon fourth generation HD Network Video Recorder Premium (NVR4) is our next generation of NVRs with the highest capacity, retention and throughput. It provides secure, reliable and scalable platforms for high performance end-to-end security solutions. Our network security recorders have Avigilon Control Center (ACC) and Avigilon Appearance Search™ technology preloaded and configured for plug-and-play network video recording and management of multi-megapixel IP cameras, up to our industry-leading 7K (30 megapixel) HD Pro.



The Avigilon HD NVR4 Premium is a 2U rack mountable recorder specifically manufactured for the Avigilon ecosystem with the flexibility to expand your surveillance system. It leverages the full power of Avigilon Control Center (ACC) and Appearance Search technology to deliver the highest available throughput, retention, and availability in the NVR4 line. The NVR4 Premium can be used individually or as a cluster of NVRs designed for IP video and video analytics metadata storage. It's backed by the Avigilon three-year warranty, extendable up to five years, which provides businesses with support and onsite parts replacement for continuous recording and retention of video while minimizing disruptions to security operations.

The HD NVR4 Premium is an out-of-the-box, ready to deploy video recording platform designed for single site surveillance or to be distributed across multiple remote sites.

KEY FEATURES

- Configured for and preloaded with ACC™ video management software
- Natively supports Avigilon Appearance Search technology
- Up to 2100 Mbps of total throughput – simultaneous recording, playback and live streaming
- Highly scalable and flexible capacity options — from 64TB to 192TB (72 TB to 252 TB raw) of recording for long-term video retention or high camera counts
- Hot-swappable components maintain video recording and playback operations even in the event of multiple simultaneous component failures
- Separate of operating system and video storage volumes to enable independent, non-disruptive maintenance
- An easy to access and maintain 2U rack mount chassis — includes a sliding rail kit and cable management system
- A three-year warranty with on-site parts replacement service

Specifications

SYSTEM		Video Management Software	
		Avigilon Control Center™ – compatible with Enterprise, Standard and Core editions	
Network Video Streaming Performance*	Network Connection	10 GbE - with multiple network connections	1 GbE
	Recording Data Rate	Up to 1500 Mbps (max 1250 Mbps per connection)	Up to 600 Mbps
	Playback and Live Streaming	Up to 600 Mbps (while simultaneously recording video)	Up to 600 Mbps
Recording Storage Capacity		Up to 180 TB raw, 157 TB effective (RAID 6), or 252 TB raw, 192 TB effective (RAID 60)	
Hard Disk Drive Configuration		Video data — up to 18 x large form factor near-line SAS hard disk drives, hot-swappable, RAID 6 or RAID 60 Operating system — 2 x M.2 SSD drives, RAID 1	
Network Interface		2 x 10 GbE SFP+ ports (transceivers not included) 2 x 1 GbE RJ-45 ports (1000Base-T)	
Memory		32GB DDR4	
Operating System		Microsoft Windows Server 2016	
Processor		Intel® Xeon®	
Video Outputs		VGA	
Local Viewing		No	
Out-of-band management		iDRAC9 Express	

* These performance figures are based on validation testing by Avigilon, using Avigilon Control Center software. For more information, contact Avigilon [Sales](#).

MECHANICAL		Form Factor	
		2U rack mount chassis	
Dimensions (LxWxH)	with bezel	751.3 mm x 482 mm x 86.8 mm; 29.58" x 18.98" x 3.41"	
	without bezel	737.5 mm x 482 mm x 86.8 mm; 29.04" x 18.98" x 3.41"	
Weight		46.3 kg (102 lbs) when fully populated with hard drives	


ELECTRICAL		Power Input	
		100 to 240 VAC, 50/60 Hz, auto-switching	
Power Supply		80 Plus rating redundant, hot-swappable	
Power Consumption		Average: 429 W (1+1) (1463.8 BTU/h), Maximum: 750 W (2559.1 BTU/h)	

ENVIRONMENTAL		Operating Temperature	
		10° C to 35° C (50° F to 95° F)	
Storage Temperature		-40° C to 65° C (-40° F to 149° F)	
Humidity		10% to 80% relative humidity with 29°C (84.2°F) maximum dew point	
Operating Vibration		0.26 Grms at 5 Hz to 350 Hz	
Storage Vibration		1.88 Grms at 10 Hz to 500 Hz for 15 min	
Operating Shock		Six consecutively executed shock pulses in the positive and negative x, y, and z axes of 6 G for up to 11ms	
Storage Shock		Six consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 71 G for up to 2 ms	
Max. Operating Altitude		3,048 m (10,000 ft)	
Storage Altitude		12,000 m (39,370 ft)	

SUPPLIED ACCESSORIES		Rack Rail System	
		Sliding rail system with cable management arm. Supports: <ul style="list-style-type: none"> • Tool-less mounting in 19"-wide EIA-310-E compliant square hole and unthreaded round-hole 4-post racks • Tooled mounting in threaded hole 4-post racks 	
Bezel		1, front	
Power Cords		2	

CERTIFICATIONS		Certifications	
		UL, cUL, CE, BIS, BSMI, CCC, EAC, KC, NOM, NRCS, VCCI, RCM	
Safety		EN 60950-1:2006 / A1:2009 / A1:2010 / A12:2011 / A2:2013; UL/CSA/IEC 60950-1, 2 Ed + Am 1: 2009 + Am 2: 2013	
Electromagnetic Emissions		US CFR Title 47, FCC Part 2, 15; Canadian ICES-003(A) Issue 6; EN 55032:2012/ EN 55032:2015/ CISPR 32:2012/ CISPR 32:2015 (Class A); EN 61000-3-2:2014/ IEC 61000-3-2:2014 (Class D); EN 61000-3-3:2013/ IEC 61000-3-3:2013	
Electromagnetic Immunity		EN 55024:2010+A1:2015/CISPR 24:2010 + A1:2015	
Energy		Commission Regulation (EU) No. 617/2013	
ROHS		EN 50581:2012	

Outline Dimensions



Ordering Information

HD-NVR4-PRM-64TB	64 TB (72 TB Raw) HD NVR4 Premium with Microsoft Windows Server 2016 Avigilon Control Center
HD-NVR4-PRM-96TB	96 TB (112TB Raw) HD NVR4 Premium with Microsoft Windows Server 2016 Avigilon Control Center
HD-NVR4-PRM-128TB	128 TB (144 TB Raw) HD NVR4 Premium with Microsoft Windows Server 2016 Avigilon Control Center
HD-NVR4-PRM-157TB	157 TB (180 TB Raw) HD NVR4 Premium with Microsoft Windows Server 2016 Avigilon Control Center
HD-NVR4-PRM-192TB	192 TB (252 TB Raw) HD NVR4 Premium with Microsoft Windows Server 2016 Avigilon Control Center
Avigilon Control Center licenses must be purchased separately. Avigilon Appearance Search requires Enterprise version of ACC.	
HD-NVR4-ANK2-1	Analytics Kit for Avigilon Appearance Search software
HD-NVR4-PRM-2NDPS-AU	Redundant, hot-swappable power supply, for AU
HD-NVR4-PRM-2NDPS-EU	Redundant, hot-swappable power supply, for EU
HD-NVR4-PRM-2NDPS-NA	Redundant, hot-swappable power supply, for NA
HD-NVR4-PRM-2NDPS-UK	Redundant, hot-swappable power supply, for UK
HD-NVR4-SFPPLUS-DA	SFP+ 10GbE Twinax Direct Attach Cable 3m
HD-NVR4-SFPPLUS-SR	SFP+ 10GBASE-Short Range Transceiver

